

UHP-2 CLOSED CHAMBER WELD HEADS

TIG / GTAW welding of tube to tube joints



- Fusion TIG / GTAW all position orbital welding of tubes, fittings and accessories. O.D. from $1,6 \text{ mm} / \frac{1}{16}$ " to 33,7 mm / $1\frac{1}{3}$ ".
- Perfectly adapted for joining tubes out of stainless steel, high alloy materials and titanium.
- The head clamps on both sides of the weld joint and forms a closed chamber for the shielding gas and the welding arc.
- During welding, the head body remains stationary, the electrode gear and tungsten electrode rotate around the tube.



PS type power source ideal for use with UHP weld heads

A modular concept



Electrode gear module UHP 250-2: 1/4" UHP 500-2: 1/2" UHP 1500-2: 1¹/₃"

A single drive

UNIQUE FEATURES

- Compatible for work with all series of Polysoude power sources.
- High purity gas circuit to avoid particle emission and oxidation.
- Modular concept:
 - unique drive handle
 - three electrode gear modules $\frac{1}{4}$ "; $\frac{1}{2}$ "; $\frac{1}{3}$ "
 - removable clamping cassettes.
- Non symmetrical design for welding of fittings with short stick-out.
- Titanium clamping cassettes (UHP 250-2 and 500-2) or flexible Tube Clamp Inserts - TCI's™ (UHP 1500-2) to comply with standard O.D.'s tolerances and hygienic / high purity requirements.
- Narrow weld head profile for use in areas with constrained radial and axial clearance.
- Closed loop regulation to ensure precise, constant or pulsed welding speed.
- Encoder for position based control of the welding program.
- Return-to-home feature: the electrode gear automatically returns to its loading position.

ACCESSORIES & OPTIONS for your particular needs

- Titanium clamping cassettes and Tube Clamp Inserts TCI's™ for all tube and pipe O.D.'s available both in metric and inch sizes.
- Removable Fixture-Blocks for all types of micro-fittings, providing perfect tube end centring, alignments and great clamping force (UHP 500-2).
- Interchangeable electrode gear modules $\frac{1}{4}$ "; $\frac{1}{2}$ "; $\frac{1}{3}$ " for optimised use of axial and radial clearance around the weld joint.
- Extension cable (15 m).
- Manual tack welding kit including water-cooled TIG / GTAW torch.
- Dual weld head switch box.
- Compact brief-case for packing, transport and storage.
- Tungsten electrodes, pre-sharpened and pre-cut.
- Tool kit for daily operations.



UHP 250-2 with clamping cassette





UHP 500-2 with clamping cassette



UHP-2 CLOSED CHAMBER WELD HEADS

WELD HEAD SPECIFICATION





UHP 1500-2



Reducing elbow



Fixture-Block for UHP 500-2



Union tee

Removable Fixture-Blocks for all types of micro-fittings, providing perfect tube end centring, alignments and great clamping force (UHP 500-2)

Cable length: 5,5 m

Туре	Tube O.D. mm / inches	
	from - to	
UHP 250-2	1,60 – 6,35 mm	$^{1}/_{16}" - ^{1}/_{4}"$
UHP 500-2	3,00 – 12,70 mm	$^{1}/_{8}" - ^{1}/_{2}"$
UHP 1500-2	6,00 – 33,70 mm	$^{1}/_{4}" - 1^{1}/_{3}"$